


**SAFE**  
Metalldetektierbar



ca. 84° Shore A

Empf. Vorspannung 3...8 %


## PU 80 A SAFE capriblau glatt



Artikel Nr.	Profil- abmessung mm	Material- querschnitt cm <sup>2</sup>	ca. Gewicht kg/100 m	Gebindegröße		Empf. Mind.- Scheiben-∅		Fmax/Riemen (Stoß)*	
				m	ft	mm	inch	kg	lbs
FBKJ6YLGM	6 x 4 (Y)	0,19	2,3	100	328	40	1,6	4,6	10,2
FBKJ8MLGM	8 x 5 (M)	0,32	4,0	100	328	45	1,8	7,7	16,9
FBKJ10ZLGM	10 x 6 (Z)	0,48	6,0	50	164	55	2,2	11,5	25,3
FBKJ13ALGM	13 x 8 (A)	0,82	10,0	50	164	85	3,3	19,7	43,3
FBKJ17BLGM	17 x 11 (B)	1,46	18,0	50	164	110	4,3	35,0	77,1
FBKJ22CLGM	22 x 14 (C)	2,40	29,0	50	164	150	6,0	57,6	126,7

Reibwerte  $\mu$ : Stahl: ca. 0,65 | PE: ca. 0,35 | HDPE: ca. 0,30 | FDA/EC/USDA-konform

\* = bei Reibwert  $\mu$ :0,5



ca. 84° Shore A

Empf. Vorspannung 4...8 %

## PU 80 A transparent glatt



Artikel Nr.	Profil- abmessung mm	Material- querschnitt cm <sup>2</sup>	ca. Gewicht kg/100 m	Gebindegröße		Empf. Mind.- Scheiben-∅		Fmax/Riemen (Stoß)*	
				m	ft	mm	inch	kg	lbs
FBKP80A06TR	6 x 4 (Y)	0,19	2,3	100	328	40	1,6	6,2	13,7
FBKP80A08TR	8 x 5 (M)	0,32	4,0	100	328	45	1,8	10,3	22,6
FBKP80A10TR	10 x 6 (Z)	0,48	6,0	50	164	55	2,2	15,4	33,9
FBKP80A13TR	13 x 8 (A)	0,82	10,0	50	164	85	3,3	26,3	57,9
FBKP80A17TR	17 x 11 (B)	1,46	18,0	50	164	110	4,3	46,9	103,1
FBKP80A22TR	22 x 14 (C)	2,40	29,0	50	164	150	5,9	77,0	169,5
FBKP80A32TR	32 x 20 (D)	5,00	62,0	25	82	220	8,7	160,5	353,1

Reibwerte  $\mu$ : Stahl: ca. 0,65 | PE: ca. 0,35 | HDPE: ca. 0,30 | FDA/EC/USDA-konform

\* = bei Reibwert  $\mu$ :0,5



ca. 84° Shore A

Empf. Vorspannung 4...8 %

## PU 80 A orange glatt



Artikel Nr.	Profil- abmessung mm	Material- querschnitt cm <sup>2</sup>	ca. Gewicht kg/100 m	Gebindegröße		Empf. Mind.- Scheiben-∅		Fmax/Riemen (Stoß)*	
				ft	(m)	mm	inch	kg	lbs
FBJ6YOG	6 x 4 (Y)	0,19	2,3	100	30,48	40	1,6	6,2	13,7
FBJ8MOG	8 x 5 (M)	0,32	4,0	100	30,48	45	1,8	10,3	22,6
FBJ10ZOG	10 x 6 (Z)	0,48	6,0	100	30,48	55	2,2	15,4	33,9
FBJ13AOG	13 x 8 (A)	0,82	10,0	100	30,48	85	3,3	26,3	57,9
FBJ17BOG	17 x 11 (B)	1,46	18,0	100	30,48	110	4,3	46,9	103,1
FBJ22COG	22 x 14 (C)	2,40	29,0	100	30,48	150	5,9	77,0	169,5
FBJ32DOG	32 x 20 (D)	5,00	62,0	100	30,48	220	8,7	160,5	353,1

Reibwerte  $\mu$ : Stahl: ca. 0,65 | PE: ca. 0,35 | HDPE: ca. 0,30 | FDA/EC/USDA-konform

\* = bei Reibwert  $\mu$ :0,5