



Available length and versions	T1/2" CLA	Comment
Standard lengths	rolls of 50 or 100 m	-
Cut to lengths / lengths > 100 m	on request	-
In-between belt widths / other widths	not available	-
minimum length endless joined (b=101,6 mm)	1000 mm	-
minimum length endless joined (b=152,4 mm)	-	-
Standard material	TPUCLA	-
Steel tension member	Standard	-
E tension member	not available	-
Stainless steel cord	not available	-
PAZ	available	-
PAR	not available	-
PAZ-PAR	available	-
DL / DL-PAZ	not available	-
DR / DR-PAZ	not available	-
T / T-PAZ	available	-

Belt widths b [mm] (In-between belt widths on request)			
25.4	50.8	76.2	101.6

Tooth shear strength (specific belt tooth load bearing)							
R.p.m. n [min-1]	F _{tspez} [N/cm]	R.p.m. n [min-1]	F _{tspez} [N/cm]	R.p.m. n [min-1]	F _{tspez} [N/cm]	R.p.m. n [min-1]	F _{tspez} [N/cm]
0	44	800	28.2	2,000	22.1	5,000	15.74
20	42.7	900	27.5	2,200	21.5	5,500	15.07
40	41.6	1,000	26.8	2,400	20.9	6,000	14.46
60	40.7	1,100	26.2	2,600	20.3	6,500	13.89
80	39.8	1,200	25.6	2,800	19.81	7,000	13.36
100	39.1	1,300	25.1	3,000	19.33	7,500	12.87
200	36.1	1,400	24.6	3,200	18.88	8,000	12.42
300	34.1	1,500	24.1	3,400	18.45	8,500	11.99
400	32.5	1,600	23.7	3,600	18.05	9,000	11.58
500	31.1	1,700	23.2	3,800	17.68	9,500	11.19
600	30	1,800	22.9	4,000	17.32	10,000	10.83
700	29.1	1,900	22.5	4,500	16.49		

T1/2" CLA			Admissible tensile force of the belt F_{adm} / belt weight			
belt width		b [mm]	25.4	50.8	76.2	101.6
M	E / Steel tension member	F_{Tadm} [N]	2,200	4,400	6,600	8,800
	Specific elasticity (E- / Steel tension member)	C_{spez} [N]	$0.55 \cdot 10^6$	$1.1 \cdot 10^6$	$1.65 \cdot 10^6$	$2.2 \cdot 10^6$
	Stainless steel cord	F_{Tadm} [N]	-	-	-	-
	Specific elasticity (stainless steel tens. m.)	C_{spez} [N]	-	-	-	-
V	E / Steel tension member	F_{Tadm} [N]	1,100	2,200	3,300	4,400
	Stainless steel cord	T_{adm} [N]	-	-	-	-
Belt weight (Standard)		[kg/m]	0.108	0.216	0.324	0.432
Belt weight (DL)		[kg/m]	-	-	-	-
Belt weight (DR)		[kg/m]	-	-	-	-
Belt weight (T)		[kg/m]	0.169	0.338	0.507	0.676

T1/2" CLA		Flexibility (Minimum number of teeth / minimum diameter)											
		Steel tension member				E / Steel tension member				Stainless steel cord			
		Standard	DL	DR	T	Standard	DL	DR	T	Standard	DL	DR	T
	Minimum number of teeth without contraflexure (z_{min})	14	-	-	20	-	-	-	-	-	-	-	-
	Minimum diameter of tensioning roller without contraflexure (d_{min} [mm])	60	-	-	80	-	-	-	-	-	-	-	-
	Minimum number of teeth with contraflexure (z_{min})	20	-	-	20	-	-	-	-	-	-	-	
	Minimum diameter of tensioning roller with contraflexure (d_{min} [mm])	80	-	-	80	-	-	-	-	-	-	-	